

8. (Amended) A pad for a tree shaking apparatus comprising:

a resilient polymeric web adapted to wrap around a portion of a tree trunk when operating the tree shaking apparatus, and

a pair of parallel end sections attached to opposite ends of said web, each of said end sections defining a bore extending longitudinally therethrough for receiving a mounting member of the tree shaking apparatus.

2. A pad as defined by claim 8 wherein said bores are approximately parallel to each other.

3. A pad as defined by claim 8, wherein said web is fabricated from polyurethane.

4. A pad as defined by claim 8 wherein said end sections are fabricated from polyurethane.

5. A pad as defined by claim 8 wherein at least one aperture is positioned adjacent to each end section for providing strain relief in the pad during operation of the tree shaking apparatus.

6. A pad as defined by claim 8 wherein said end sections and said web are fabricated from polyethylene.

9. (Amended) A pad for a tree shaking apparatus comprising:
10 a resilient polymeric web adapted to wrap around a portion of a tree
trunk, and
a pair of parallel end sections attached to opposite ends of said web,
each of said end sections defining a bore extending longitudinally therethrough for
receiving a mounting member of the tree shaking apparatus; and
15 a pair of apertures approximately parallel and adjacent to the bore of
each of said end section extending at least part way through said pad.

10. (New) A pad for a tree shaking apparatus comprising:
a resilient polymeric web adapted to wrap around a portion of a tree
20 trunk when operating the tree shaking apparatus, said web defining a first surface to
contact a tree and an opposing surface, said opposing surface being generally concave
when at rest; and
a pair of parallel end sections at opposite ends of said web, each
defining a bore extending longitudinally therethrough for receiving a mounting member
25 of the tree shaking apparatus.

11. (New) The pad for a tree shaking apparatus of claim 10 wherein said
first surface is generally planar.

30 12. (New) The pad for a tree shaking apparatus of claim 10 wherein said
first surface is less concave than said opposing surface.

13. (New) The pad for a tree shaking apparatus of claim 10 wherein said
pad is formed in a single piece.

5

14. (New) The pad for a tree shaking apparatus of claim 13 wherein said pad is formed in a single piece from polyurethane or polyethylene.

10

15. (New) The pad for a tree shaking apparatus of claim 13 further comprising an aperture approximately parallel to said bores through said pad in a transition area between said web and said end section.

15

20

25